



FLEXICOAT- SPORT COAT SPC 1000

DURABLE, ANTI-SLIP TEXTURE COATING FOR CONCRETE AND MASONARY SURFACES.

USES

- Sport courts and recreational areas.
- Bicycle lanes, driveways, walkways, sidewalks and ramps.
- Pool decks, patios and porches.
- Concrete steps.

FEATURES

- Self - levelling.
- Easy to apply.
- Homogenous in appearance.
- Good adhesion, withstand water soaking.
- Good resistance to potential spills of fuels and lubricants.

APPLICATION METHOD

SURFACE PREPARATION

- Please ensure that the surface is sound, cohesive, clean, dry and free of dust.
- It is important to prime the surface before application. use acrylic type primers only.
- Smooth concrete surface needs to be roughen to allow for proper adhesion.
- No priming required for newly laid bituminous surface.

APPLICATION

- Mix thoroughly with a mechanical stirrer at low speed before use.
- Pour and spread **FLEXICOAT SPORT** using a rubber drag any other appropriate tools to form a thin, relatively uniform . Let each coat to cure for 24 hours before applying the next coat. Recommended thickness: > **2mm** (A thickness of 0.6 mm is achieved with coverage of $1\text{kg}/\text{m}^2$)

Recommended Coverage:

1 ST Coat:	0.7 - 1.0	kg/ m ² (For slightly rough surface)
	1 - 2.0	kg/ m ² (For more rough or porous surface)
2 nd Coat:	0.7 - 1.0	kg/ m ²

REMARKS

- It is advisable to apply **FLEXICOAT SPORT** at temperatures between 10 - 35°C . Do not apply if rain is expected within 24 hours.
- Ensure there is adequate ventilation during application to promote proper curing.
- Water can be added as needed **FLEXICOAT SPORT** as it may affect adhesion performance.
- Store in a cool, dry place.

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100 / 6364 5060 / 6367 3676 Fax: (65) 6364 0629

war99@singnet.com.sg www.warrior.com.sg





FLEXICOAT- SPORT COAT SPC 1000

DURABLE, ANTI-SLIP TEXTURE COATING FOR CONCRETE AND MASONRY SURFACES.

TECHNICAL DATA

- Maximum aggregate size UNE EN 933-1: 1mm
- Curing time @ 22°C and 55% RH 24 hours for foot traffic
- Colours Oxide Red, Green, Yellow and Grey
- Storage Life 9 months

PACKING: **SPC 1000** 5 kg-pail, 20 kg-pail, 200 kg-drum.

SAND GRIT SG 100 5 kg-bag, 25 kg-bag.



Disclaimer: *The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte. Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte. Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user.*

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100 / 6364 5060 / 6367 3676 Fax: (65) 6364 0629

war99@singnet.com.sg www.warrior.com.sg

