



CORO COAT CX1

1-Part Water Based Acrylic Anti-Corrosion

Uses:

1. Anti-corrosion coating is applied on metal, steel deck for ships, yachts & boats.
2. Excellent for machine parts during storage.

Features:

1. Water based 1-parts system, free from solvent.
2. Non-flammable, non-toxic and non-hazardous.
3. It protects against salt, hard use and corrosion.
4. No primer necessary. Fast drying less than 20 minutes
5. Flexible coating that will absorb movement well.
6. For use above the water line.



Application Method:

1. Surface Preparation, Metal parts are to be clean and free from oil.
2. Remove oil, grease and other contaminations with a suitable detergent, followed by rinsing with water at high pressure.
3. Use directly from the container.
4. Apply with a paint brush, Roller or Spraying machine in 2 coats..



Drying and Curing Time

1. Painting should not be carried out before the rain.
2. Theoretical Coverage: 300 g / m2 @ 50 micron
3. Recommended Dry Film Thickness: 120-150 m 2 to 3 coats
4. Dry to the touch: 30 minutes
5. Hardening Time: 2 hours
6. Full Curing till insoluble in water: 3 hours
7. Recoating Intervals: 30 minute minimum, Maximum unlimited



WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

Fax: (65) 6364 0629

war99@singnet.com.sg

www.warrior.com.sg

bizSAFE₃



CORO COAT CX1

1-Part Water Based Acrylic Anti-Corrosion

Weather Conditions:

It is recommended to carry out painting in fair weather.

Paint works should not be carried out in damp or rainy days.

- Air temperature: 10 - 40 °C
- Relative Humidity: 35 – 75 %
- Surface temperature: 5 °C to approximately 40 °C.

Cleaning of Equipment

1. Immerse the spray gun in clean water during the intervals between spraying, to prevent clogging of the nozzle. Rinsing water should be replaced periodically.
2. When painting is completed, the entire set of equipment should be cleaned thoroughly with water + detergent.
3. Extra care should be taken when cleaning the spray gun to prevent clogging of the nozzle.

Technical Data:

1. Toxicity: Free from copper, lead, mercury and tin,
2. Colours: Grey Viscous Liquid
3. Shelf Life: 24 months

Storage:

1. The product is guaranteed when stored under normal temperature and humidity in sealed condition.
2. No special precautions are required against fire.
3. If there is long-term exposure to frost during storage, the Liquid Solution may be separated into 2 phases. The liquid solution should be stirred before use to ensure homogeneity.

Packing: 5 kg-pail, 20 kg-pail.

Disclaimer:

The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user



WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

Fax: (65) 6364 0629

war99@singnet.com.sg

www.warrior.com.sg

