



USP ULTRA SMOOTH PLASTER

Exterior & Interior Wet Putty for Wall and Ceiling

Uses

- * A White colour Wet Finishing Putty, for plastering over cement-sand rendered wall or ceiling in a one-step operation, achieving ultra-smooth finish.
- * Color Paste can be added.
- * Patching of holes, fine crack, and dent, on cement and gypsum surface.
- * Excellent for grouting wall tile joints.

Features

- * Bond strength exceeds 0.8 mpa, hard and breathable, it does not shrink and crack and is non powdery. Water and alkaline resistance.
- * Water-based Silicate wall finishing material. It can be painted without a sealer coat.



Application Methods

- * Dampen the wall surface before troweling smooth with **USP WALL PLASTER**.
- * Apply 2 to 3 coats, about 2 to 3 mm per coat. When it is about 80 % dry and harden; use a steel trowel to press and smoothen the surface, to achieve a smooth mirror finish.
- * Scratch mark can be re-smoothing by wetting with a paintbrush. No sanding and painting is needed.
- * Old Wall surface usually has acidic residue, treat the surface with sealer (e.g. W1 CEMENT STRENGTHENER) to prevent yellowing.
- * For wall with gypsum cornices, **USP WALL PLASTER** can be diluted with water and spray or roll over the entire wall to achieve even finishes.

Coverage

- 2 m²/ 1 kg / 2 mm thick.
- 10 m² / 5 kg / 2 mm thick.
- 40 m² / 20 kg / 2 mm thick.

Technical Data

- Colour: White colour paste
- Shelf Life: Tightly cap can last for many years.

Packing

- 1 kg-tub, 5 kg-tub, 20 kg-pail

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

Fax: (65) 6364 0629

war99@singnet.com.sg

www.warrior.com.sg

