



# CX 3 CORO COAT - ZINC COAT

## 1 Parts Solvent Acrylic Anti-Corrosion Coating

### Uses:

1. Metal roof and structures, industrial equipment, ship deck and machinery.
2. Dark grey antique colour for hand-railings and lamp posts.
3. Cast Iron pipes in the wet bathroom.

### Features:

1. The zinc content will sacrifice itself to protect the iron surface from rusting.
2. It is both an undercoat and finishing coating, saving on time labour.

### Application Method:

1. De-rust metal surface by high-pressure water jet, wire brush or using chemicals (HCl, H<sub>2</sub>SO<sub>4</sub>, Citric Acid, etc).
2. To promote adhesion, the metal surface can be treated with phosphatizing chemicals.
3. It can be coated directly over light rust area,
4. High penetration property to give good adhesion and rust protection.

### Technical Data:

- |                         |                                       |
|-------------------------|---------------------------------------|
| 1. Colour:              | Greyish Black                         |
| 2. Coverage:            | 4 m <sup>2</sup> per kg (theoretical) |
| 3. Film Thickness:      | 15 micron                             |
| 4. Drying Time:         | 15 minute to dry, 2 hour to cure      |
| 5. Re Coating Interval: | 12 hours to a maximum of 90 days      |
| 6. Diluent:             | Xylene, toluene                       |
| 7. Flash Point:         | Flammable at 40 °C                    |
| 8. Storage Life:        | 3 years                               |
| 9. <b>Packing:</b>      | 5 kg-tin, 20 kg-steel pail.           |

### Safety:

1. Use in well-ventilated area, avoid naked flame and smoking. Avoid skin contact.
2. Provide air ventilation during the coating process and the next 2 hours after coating.
3. always wear air masks; safety goggles, working clothes and gloves.
4. Allow spent paint in the container to harden before disposal, to avoid polluting the waterway.
5. In cases it get in contact with naked skin or the eyes, wash with water,
6. Seek medical advice in severe cases.



### WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

Fax: (65) 6364 0629

[war99@singnet.com.sg](mailto:war99@singnet.com.sg)

[www.warrior.com.sg](http://www.warrior.com.sg)





# CX 3 CORO COAT - ZINC COAT

## 1 Parts Solvent Acrylic Anti-Corrosion Coating



**Disclaimer:** *The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user*



### WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

[war99@singnet.com.sg](mailto:war99@singnet.com.sg)

Fax: (65) 6364 0629

[www.warrior.com.sg](http://www.warrior.com.sg)

