



# F1000 FLEXI CLEAR

WATER-BASED GLOSS OR MATT SEALER FOR OUTDOOR OR INDOOR USE

## USES

- As a **primer** for chalky cement surfaces
- As a **clear sealer** for car parks, slate, limestone, cement tiles, earthenware, tiles and porous surfaces
- As **external and internal wall putty** when added with calcium carbonate powder
- As **metal protection** that provides light-duty anti-rust protection

## APPLICATION METHOD

1. Cement has to be cured for at least 14 days before coating.
2. Surface to be coated has to be clean and dry for maximum absorption.
3. Seal the surface with **W4 Water Repellent** for better paint bonding and durability.
4. Dilute **F1000 FLEXI CLEAR** with suitable amount of water before applying by brush or short hair rollers. Do not apply in 1 heavy coat; it may result in white patches.

## REMARKS

- *Not suitable for coating over red brick walls. Trapped moisture will result in blistering and white patchy stains.*
- *Allow used paint in the can to dry up before disposal, to avoid polluting the waterways.*



## SAFETY PRECAUTIONS

In case of contact with skin, rinse with water immediately.

## STORAGE

**F1000** should be stored in closed containers at temperatures between +5°C and +35°C for no more than 6 months and protected from frost and direct sunlight.

**PACKING** 1-kg bottle, 5-kg carboy, 20-kg pail

## WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100 , 6364 5060 , 6367 3676

[war99@singnet.com.sg](mailto:war99@singnet.com.sg) [www.warrior.com.sg](http://www.warrior.com.sg)





# F1000 FLEXI CLEAR

WATER-BASED GLOSS OR MATT SEALER FOR OUTDOOR OR INDOOR USE

## TECHNICAL DATA

Type of Copolymer	Acrylic Copolymer, Non Yellowing
Appearance	Milky blue-white emulsion
Solid	25.0 - 27.0%
pH	7.0 - 8.0
Glass Transition Temperature	40°C
Minimum Film Forming Temperature	24°C
Finishes	Gloss or Matt
Drying time	30 minutes
Re-coating time	60 minutes
Coverage	4 to 5 m <sup>2</sup> / kg

### Disclaimer:

*The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user.*

### WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100 , 6364 5060 , 6367 3676

[war99@singnet.com.sg](mailto:war99@singnet.com.sg)    [www.warrior.com.sg](http://www.warrior.com.sg)

