



R1 ROAD MARKING PAINT

WATER-BASED ACRYLIC ROAD PAINT

USES AND FEATURES

1. A water-based coating that combines toughness, adhesion and chemical resistance
2. For carparks, warehouses and road linings



TECHNICAL DATA

- VOC: less than 255 g/L
- Volume Solids: 50% ± 2%
- Finish/Sheen: Gloss
- Typical Film Thickness: 125 microns dry (178microns wet)
- Theoretical Coverage: 3-4 m² / litre at typical film thickness

APPLICATION METHOD

- All surfaces to be coated should be clean, dry and free from contamination.
- Apply with roller or brushes.

DRYING INFORMATION

- | | <u>10°C</u> | <u>25°C</u> | <u>35°C</u> |
|--------------|-------------|-------------|-------------|
| • Touch Dry: | 50 minutes | 35 minutes | 20 minutes |
| • Hard Dry: | 4 h | 3 h | 2 h |
| • Thinner: | Water | | |

SAFETY PRECAUTIONS

Skin and eyes must avoid coming into contact with the pain.

STORAGE

Store in cool and dry conditions. Ventilate well. Keep away from heat and fire.

SHELF LIFE

12 months, minimum temperature at 25°C. Subject to re-inspection thereafter

COLOUR

White, Black, Yellow, Green, or individually blended color

Disclaimer:

The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user.

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100 , 6364 5060 , 6367 3676

war99@singnet.com.sg www.warrior.com.sg

