



# RX1 RUST CONVERTER

## ANTI-OXIDISATION COATING

### USES

1. Metal products subjected to rusting or atmospheric corrosion during storage or shipping
2. Metal roofs, ships and vehicles
3. Objects at site which are difficult to sand blast such as vehicles, trailers, fences, iron railings, sheet metal, and the outside of storage tanks
4. Used to restore and preserve iron-based items of historical importance.

### FEATURES

1. Water-based; reacts with rust to convert it to a stable compound that is resistant to water and bacterial growth.
2. Treated surfaces can be painted with either water-based or oil-based paints.

### APPLICATION METHOD

1. Wire brush away loose rust.
2. Apply directly or diluted 1 – 2 times depending on the extent of the rust.

Drying Time: 10 to 20 minutes

Re-Coating Interval: 30 minutes

Fully Cure: 24 hours

Best to apply on a dry day, above 8°C.

### COVERAGE

8 m<sup>2</sup> / 1 liter

40 m<sup>2</sup> / 5 liter

100 m<sup>2</sup> / 20 liter

### PACKING

1-litre bottle

5-litre carboy

20-litre jerry can

200-litre drum



### WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100 , 6364 5060 , 6367 3676

[war99@singnet.com.sg](mailto:war99@singnet.com.sg) [www.warrior.com.sg](http://www.warrior.com.sg)





# RX1 RUST CONVERTER

## ANTI-OXIDISATION COATING

### TECHNICAL DATA

Colour:	White colour liquid.
Viscosity:	less than 200
pH Value:	1 to 2 acidic
Film Forming:	15°C minimum
Flash Point:	210°C
Resistance to Water :	3 days
Resistance to Solvent:	3 days
Heat Resistance:	100°C
VOC:	less than 3% g / litre
Shelf Life:	12 months

### STORAGE

Keep containers tightly sealed away from extreme temperature changes and open flames.

### SAFETY PRECAUTION

1. Handle the product with care.
2. Provide adequate ventilation when applied on a large scale.
3. Do not inhale vapor.
4. Proper gloves, safety goggles and facemasks must be worn during handling.
5. Wash hands thoroughly after use.

#### Disclaimer:

*The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user.*



### WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100 , 6364 5060 , 6367 3676

[war99@singnet.com.sg](mailto:war99@singnet.com.sg)    [www.warrior.com.sg](http://www.warrior.com.sg)

