



WARRIOR S2000P PRIMER

CHRISTY PAINT PRIMER

S2000P is a penetrating and sealing primer for porous surfaces, which controls absorption and reinforces the surface of the substrates, which are to be painted with silicate-based paints such as **S2000 Silicate Paint**.

USES

- Concrete, lime, cement mortars, masonry, rendering and bricks
- Can be used on façades and internal and external walls

FEATURES

- Excellent adherence on a great range of surfaces such as mortars, brick, fiber-cement, concrete, natural and artificial stone
- Helps prevent algae growth
- Excellent sealing and impregnating power
- High penetration in the substrates, thus reinforcing them on their surfaces

APPLICATION METHOD

SURFACE PREPARATION

- Surface must be clean, dry, absorbent and free from dust and grease.
- For interior use, remove all loose plaster and apply filler as appropriate.
- Remove all old paint before applying **Silicate Paint Primer**. Gypsum surfaces require application of a polymer-based primer.
- Wash or scrape off flaking or peeling paint.
- All other surfaces should be washed down thoroughly.

INSTRUCTIONS:

Stir well before use.

Mixing ratio : **S2000 P** + **Water** = **1** + **1**

To get a consistent and even coating when applying Dark Colored Silicate Paint.

Mixing Ratio : **S2000 P** + **Water** + **Silicate Paint** = **1** + **1** + **1**

Allow the coating to dry for 24 hours before applying the 1st coat.

REMARKS

- **S2000 P** is highly alkaline. Please take care to protect all adjacent glass, metal and ceramic with masking tape before painting to avoid staining.



CERT NO.: XX-XXXX
ISO 14001 : 2004

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100 , 6364 5060 , 6367 3676

war99@singnet.com.sg www.warrior.com.sg





WARRIOR S2000P PRIMER

CHRISTY PAINT PRIMER

TECHNICAL DATA

Nature	Silicate
Diluent	Water
Application	Brush or roller
Drying time @ 20°C (Relative Humidity: 55%)	Touch Dry - 4 hours Re-painting - 24 hours
Coverage	8 - 10 m ² / litre depending on the porosity, surface texture and wastage rates.

SAFETY PRECAUTIONS

- Wear protective gear to protect the eyes and skin.
- In case of contact, rinse with water immediately.

PACKING

5-litre carboy

Disclaimer:

The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user.



CERT NO.: XX-XXXX
ISO 14001 : 2004

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100 , 6364 5060 , 6367 3676

war99@singnet.com.sg www.warrior.com.sg

