

A1 WET SKIM (278)

Premium Lime Based Ready to Use Base Coat

BASE | WHITE



Your Plastering Solutions

USES . A1 Wet Skim 288 is a Premium Lime based Ready to use base coat plaster for interior walls. Our A1 Wet Skim is specially formulated to provide user good workability and produce the best surface results . It also helps improve uneven wall surface and eliminate most cracks . Best of all it doesn't require mixing and is reusable if is not finish .

KEY FEATURES

- 1) Very Good Workability
- 2) Highest quality aesthetic finish
- 3) Ready to Use (no mixing require) & Reusable
- 4) Easy to repair

TECHNICAL DATA

Color Appearance	White
Packaging	10 kg
Usage Guide	Shake Evenly before usage .
Recommended Thickness	2 mm - 3 mm / layer (maximum 3 mm / layer)
Bond Strength	Above 0.6 N/ mm2
Coverage	Approx. 0.8m2 / kg / 1 mm thick
Storage	6 month s in its original packing (store indoor) . Keep it moist in a container with small amount of water if unfinished

APPLICATION

- 1) Shake the A1 Wet Skim 278
- 2) Pour the content into a clean bucket
- 3) Ensure surface are free from oil , grease , dust or any other foreign particles before application
- 4) Trowel at recommended thickness (2 mm - 3 mm). Ensure the second layer is dried before working on the subsequence layer.
- 5) Keep it moist in a container with small amount of water if unfinished.
- 6) Pour the water out and continue usage .





A1 WET SKIM (278)

READY TO USE SKIM COAT PASTE : BASE COAT PLASTER

Approx. Coverage : 4m² / 10kg bag @ 2mm per layer
Recommended Thickness : 2mm per layer
Colour : White

A1 WET SKIM (288)

READY TO USE SKIM COAT PASTE : TOP COAT PLASTER

Approx. Coverage : 8m² / 10kg bag @ 1mm per layer
Recommended Thickness : 1mm per layer
Colour : White

1. SHAKE IT



2. POUR IT



3. USE IT

