



QP1 QUICK PLUG

MATERIAL SAFETY DATA SHEET

LAST REVISED: 2 SEPTEMBER 2026

SUBSTANCE/PREPARATION AND COMPANY IDENTIFICATION

Company:

Warrior Pte Ltd

Contact address:

17 Marsiling Industrial Estate Road 1 #01-11

Singapore 739279

Telephone: +65 6364 5100

E-mail address: war99@singnet.com.sg

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Calcium aluminate clinker compound 100 wt %

Hazardous Component Name	CAS-No.	EC-No.	Content	Identification
Calcium-aluminate-clinker	65997-16-2	266-045-5 100	100%	Not Relevant

HAZARDOUS IDENTIFICATION

Danger characterization: Not relevant

Special danger remarks

- When mixed with water, the product may cause temporary irritation to the eye and skin in case of extended contact. In spite of the pH (11-11.5), the alkaline reserve is limited.
- The product is not classified as irritant according to Directive 67/548/EEC or Regulation (EC) No 1272/2008.

FIRST-AID MEASURES

General remarks

Not relevant

After inhalation

Reference to medical instruction

After skin contact

Wash off immediately and thoroughly with abundant water, seek medical advice if necessary.

After eye contact

In case of eye contact wash off immediately and thoroughly with abundant water and seek medical advice (S26).

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

war99@singnet.com.sg www.warrior.com.sg

bizSAFE₃



QP1 QUICK PLUG

MATERIAL SAFETY DATA SHEET

After swallowing

Rinse out mouth, drink water, cause no vomiting and consult a physician.

FIRE-FIGHTING MEASURES

Product is incombustible.

ACCIDENTAL RELEASE MEASURES

Man-related protective measures

Avoid skin and eye contact, avoid dust, provide sufficient ventilation / sufficient breath protection.

Environment protection measures

Avoid uncontrolled entry into the sewage system or into the outfall drain, especially after uncontrolled water addition.

Procedures for cleaning / absorbing

Pick up mechanically (dry).

Additional remarks

Hardens after contact with water after 20 minutes, and can be disposed like concrete afterwards.

HANDLING AND STORAGE

Handling

Instructions for safe handling

- Avoid dust development.
- Avoid skin and eye contact.
- During work, avoid skin contact through use of appropriate protective clothing.

Advice for fire and explosion protection

Not relevant

Storage

Requirements on store-rooms: Protected from moisture in closed rooms and containers and tanks. Dust precipitation according to "BlmSchG" or "TA Luft", or according to relevant national regulations.

Handling

- Handle in well ventilated areas. Avoid handling which leads to dust formation.
- Dust mask and safety goggles are recommended as fine powder can become airborne and may be irritating to the eyes and nose.
- This product should not be spilled, dumped or flushed into sewers or public waterways. Any spilled powder should be swept up.

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

war99@singnet.com.sg www.warrior.com.sg



QP1 QUICK PLUG

MATERIAL SAFETY DATA SHEET

EXPOSURE CONTROLS/ PERSONAL PROTECTION

Additional instructions for planning technical plants

Not relevant

Components with occupational related and controlled limit values

CAS-No.	Name of Substance	Kind of Limit Value	Value	Unit
65997-16-2	Calcium Aluminate Cement	General Dust Limit	600%	mg/m ³ (A)

Values According to TRGS 900

Personal protective equipment

Breath protection

Leaflet BGR 190 „Rules for the use of respiratory equipment“, Hauptverband d. gewerbl. BG*: e. g., particle filtrating half mask or particle filter P1-P3 #

Hand protection

Leaflet BGR 195 „Rules for the use of protective gloves“, Hauptverband d. gewerbl. BG: e. g., when preparing mortar or concrete, wear nitrile impregnated cotton gloves with CE mark #

Eye protection

Leaflet BGR 192 „Rules for the use of eye and face protection“, Hauptverband d. gewerbl. BG: e.g. protecting goggles with vision screen, type X ZZ 3 or 4 #

Body protection

Not relevant

General protective and hygienic measures

Skin protection according to skin protection plan following Leaflet BGR 197 „Rules for skin protection“, Hauptverband d. gewerbl. BG #

* = German Federation of statutory accident insurance institutions for the industrial sector

= or according to relevant national regulations

PHYSICAL AND CHEMICAL PROPERTIES

Form: powder

Color: grey

Odor: none

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

war99@singnet.com.sg www.warrior.com.sg

bizSAFE₃



QP1 QUICK PLUG

MATERIAL SAFETY DATA SHEET

Safety Relevant Data

	Value/Range	Unit	Method (67/548/EG)
Change of status/melting point	1270 - 1440	°C	Not Relevant
Flash Point		°C	Not Relevant
Flammability (solid, gaseous)			Not Relevant
Flammable Temperature		°C	Not Relevant
Auto Flammability		°C	Not Relevant
Explosion Risk			Not Relevant
Explosion Limits			Not Relevant
Vapour Pressure			
Density	3.2, T = 20°C	g/cm ³	
Water Solubility (depending on product, degree of hydration)	up to 1.5, T = 20°C	g/l	
pH-value	11.0 - 11.5, T = 20°C		Depending on product, saturated solution

STABILITY AND REACTIVITY

Not Relevant

TOXICOLOGICAL INFORMATION

Toxicological tests

Acute toxicity : In-vivo-animal tests showed no acute dermal toxicity.
Specific symptoms in animal tests : Not relevant
Irritant/etching effect : Not relevant

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

war99@singnet.com.sg www.warrior.com.sg





QP1 QUICK PLUG

MATERIAL SAFETY DATA SHEET

Sensitization

Not tested

Cancerogenic, genetically modifying and reproduction endangering effects

Not relevant

Practical experience

Classification-relevant observations

Not relevant

Other observations

When mixed with water, the product may cause temporary irritation to the eye and skin in case of extended contact. Mechanical skin stress at the same time is able to intensify such effects.

ECOLOGICAL INFORMATION

Information on elimination (persistence and degradation)

Not relevant; inorganic mineral building material

Behavior in environmental compartments

Not relevant, inorganic mineral building material

Eco-toxicity effects

Possible only in case of unintentional release of larger quantities in combination with water because of a higher pH-value.

Further ecological remarks

No data available

DISPOSAL CONSIDERATIONS

Product (unused residue)

Recommendation: Further use possible after picking-up dry

Waste code no.: Not relevant

Product (after addition of water, hardened)

Recommendation: After addition of water disposal like concrete

EWC waste code no.: 170101 concrete
(simplified proof in case of more than 5 tons per year and producer)

Impure packaging

Recommendation:

When taking back the (sale) packaging, a dry removal of attached remainder of the preparation is possible.

Recommended cleaner : Not relevant

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

war99@singnet.com.sg www.warrior.com.sg

bizSAFE₃



QP1 QUICK PLUG

MATERIAL SAFETY DATA SHEET

TRANSPORTATION INFORMATION

National Regulation

Identification

Employment limitations:	Not relevant
Regulation for interference:	Not relevant
Classification according to VbF:	Not relevant
Technical instruction "TA Luft":	No. 5.2.3
Water endangering class:	WGK1 (slightly water endangering)

Other regulations, limitations and prohibiting orders

Industrial medical principles and regulations of labour protection (VBG, BGR leaflets and other), or according to relevant national regulations.

REGULATORY INFORMATION

State Regulations

The following statements are provided under the California State Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer. This product contains a chemical known to the state of California to cause reproductive/developmental effects.

NFPA Hazard codes:

Health: 3 Fire: 0 Reactivity: 0 Special:

OTHER INFORMATION

- Any other intended applications should be discussed with the manufacturer.
- If you have any queries relating to this MSDS, its contents or any other product safety related questions, please write to the following e-mail address: war99@singnet.com.sg
- The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. The data do not describe the product's properties (product specification). Neither should any agreed property nor the suitability of the product for any specific purpose be deduced from the data contained in the safety data sheet. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

war99@singnet.com.sg www.warrior.com.sg

bizSAFE₃