



S100 SOLAR GUARD

HEAT REFLECTING AND INSULATING PAINT TO KEEP BUILDINGS COOL

USES

- Thermal reflector for rooftops and exterior walls
- Use on clay, metal, wood and cement surfaces
- Used as UV-protective coating for most bitumen and PU coatings to extend service life

FEATURES

- Anti-infrared rays & low heat conductivity hollow ceramic particle added to reduce indoor temperature. Keeps the building very cool.
- Breathable and high adhesion to substrate
- Low dirt pick-up due to non-static property
- Polymer-based for metal surfaces
- Silicate-based for cement surface; low water permeability
- Water-based; tools used can be cleaned easily
- User-friendly, non-toxic and environmentally friendly



APPLICATION METHOD

- Ensure surfaces to be treated are clean and dry.
- Apply with roller, brush or spray gun.
- Apply S100 evenly on surface. Thin multi-coatings are recommended as single heavy coatings may crack.
- Allow to dry for 30 minutes before applying the next coat.
- Clean tools with water after use.
- Coverage: 2 m² / kg (2 coats, thickness 0.3 - 0.4 mm)

TECHNICAL DATA

Comparison of Surface Temperature of Various Substrates

TYPES OF SURFACES	UNCOATED	COATED WITH S100	COATED WITH A TOP BRAND PAINT
RESULT	68°C	42°C	50°C
TYPE OF TEST	Surface exposed to afternoon sun for 1 hour (13:00, Singapore)		
Heat Transfer Coefficient	0.065 watt/m. K. ASTM C518.04		



WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100

war99@singnet.com.sg www.warrior.com.sg

