



SPR1000 PCE SUPER PLASTICISER

MODIFIED HIGH-RANGE WATER REDUCING ADMIXTURE FOR CONCRETE

USES

Suitable for precast concrete, cast-in-situ concrete, reinforced concrete and pre-stressed concrete such as high-speed railways, passenger railway lines, industrial and civil construction, bridges, port terminals, airports and so on.

FEATURES

1. This 3rd generation super effective de-watering agent is a synthesised Sulfonated Hydrocarbon complex polymer. It **reduces slump loss** of concrete. Keeps about 75 - 90% of the primary slump within 2 hours.
2. Can be formulated to **increase slump quality** according to requirement and keep primary slump 90% within 5 hrs
3. **Reduces water consumption** and **improves concrete strength**
4. **Remarkably reduces primary heat of hydration** and hydration temperature peak and also **delays the appearance of temperature peak**
5. **Prolongs the work time** of various kinds of flowing concrete and **ensures the quality** of concrete construction
6. **Lower content of chlorine ion and alkali** in favor of concrete durability
7. **Non-pollution** during production process; an **environment-friendly product** without formaldehyde
8. **Does not have corrosive effect** on reinforced steel bars

APPLICATION METHOD

Dosage: **0.3% to 0.5% of SPR 1000** based on the weight of cement
or **300 g /100 kg Cement Weight**

TECHNICAL DATA

Appearance: Clear Straw Colour Liquid
pH value: 7 – 8

STORAGE

Store in cool and dry place. Keep out of direct sunlight.

SHELF LIFE

1 year



Disclaimer:

The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user.

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 #01-11 Singapore 739279

Tel: (65) 6364 5100 , 6364 5060 , 6367 3676

war99@singnet.com.sg

www.warrior.com.sg





SPR1000 PCE SUPER PLASTICISER

MODIFIED HIGH-RANGE WATER REDUCING ADMIXTURE FOR CONCRETE

CONCRETE WORKABILITY

1. **SPR 1000 Superplasticizer** will improve the long term slump-retention property of concrete.
2. There is almost no slump loss in half an hour and little slump loss in 1 hour.
3. Meanwhile, it has the characteristics of low dosage, high water reducing rate and low shrinkage.
4. The fluidity of concrete is improved greatly and the concrete remains workable for a long time.
5. Simultaneously, the workability and physical properties are improved, and the engineering quality is guaranteed and improved.

			Standard	Results
Water-Reducing Rate		%	Not less than 25	26
Ratio of Bleeding Rate		%	Not greater than 60	26
Air Content		%	≤ 6.0	1.6
PH Value			6.0-7.0	5.8
Fluidity of Cement Paste		mm	≥ 220	280-310
Difference in Setting Time	Initial Setting Time	min	- 90~+120	- 25
	Final Setting Time	min		- 17
Ratio of Compressive Strength	1d	%	Not less than 170	221
	3d	%	Not less than 160	196
	7d	%	Not less than 150	217
	28d	%	Not less than 140	160
Slump Variation (1 h)		mm	≤ 80	20
Effect on Reinforcement Corrosion			Non Corroding	Non Corroding

WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 #01-11 Singapore 739279

Tel: (65) 6364 5100 , 6364 5060 , 6367 3676

war99@singnet.com.sg

www.warrior.com.sg

