



# WALLTEX

WATER-BASED ACRYLIC PAINT FOR INTERIOR AND EXTERIOR USE

## THE PROFESSIONAL PAINTER'S CHOICE OF LOW-COST PAINT

- Excellent 1 coat coverage; direct onto cement without primer
- Resists and repels water
- Strong bonding; resists washing and brushing
- Can be used for road marking
- Ideal for commercial & residential properties
- Easy to apply by brush, roller or spray



## MATTE FINISH

Silky-smooth texture, washable and can be tinted with color (both inorganic and synthetic pigments.)

## APPLICATION METHOD

### Surface Preparation

- Priming is needed if the surface is powdery.
- Test paint on a small area and do a pull-out tape test before painting the whole area.

**Re-Coating Time** 30 minutes to 1 hour

**Diluent** Water

### Drying and Curing Time

1. Painting should not be carried out before the rain.
2. Theoretical Coverage: 300 g / m<sup>2</sup> @ 50 micron
3. Recommended Dry Film Thickness: 120-150 m 1 to 2 coats
4. Dry to the touch: 30 minutes
5. Hardening Time: 2 hours
6. Full Curing till insoluble in water: 3 hours
7. Recoating Intervals: 30 minute minimum; maximum unlimited



Testing against algae resistance

## WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100, 6364 5060, 6367 3676

[war99@singnet.com.sg](mailto:war99@singnet.com.sg) [www.warrior.com.sg](http://www.warrior.com.sg)



CERT NO. XX-XXXX  
ISO 14001 : 2004



# WALLTEX

WATER-BASED ACRYLIC PAINT FOR INTERIOR AND EXTERIOR USE

## IDEAL APPLICATION CONDITION

- It is recommended to carry out painting in fair weather.
- Paint works should not be carried out on damp or rainy days.
- Air temperature: 10 - 40°C
- Relative Humidity: 35 - 75 %
- Surface temperature: 5°C to approximately 40°C

## CLEANING AND MAINTENANCE

1. Immerse the spray gun in clean water during the intervals between spraying to prevent clogging of the nozzle. Rinsing water should be replaced periodically.
2. When painting is completed, clean equipment thoroughly with water and detergent.
3. Extra care should be taken when cleaning the spray gun to prevent clogging of the nozzle.

## TECHNICAL DATA

1. Toxicity: Free from copper, lead, mercury and tin
2. Colours: White, cream, beige viscous Liquid
3. Shelf Life: 24 months

## STORAGE

1. Store under normal temperature and humidity in sealed condition.
2. No special precautions are required against fire.
3. If there is long-term exposure to frost during storage, the liquid solution may be separated into 2 phases. Stir before use to ensure homogeneity.

**PACKING:** 1-kg pail, 5-kg pail, 20-kg pail

### Disclaimer:

*The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user.*

## WARRIOR PTE LTD

Blk 17 Marsiling Industrial Estate Road 1 # 01-11 Singapore 739279

Tel: (65) 6364 5100 , 6364 5060 , 6367 3676

[war99@singnet.com.sg](mailto:war99@singnet.com.sg) [www.warrior.com.sg](http://www.warrior.com.sg)

